





新焊接技術之絲攻刀具
Carbide tap small size for precision operation

Roll Tap Series 擠壓型絲攻

Tap Features 絲攻功能

- Diameter 柄徑：M0.6 ~ M6.
- Reduce resistance of broken. 降低抗折
- Material 材料：Carbide+Stainless. 鈎鋼+不繡鋼
- Enhance precision & precentage of thread 提高精度和螺紋的百分比
- Guaranteed 25000 hole /pc for Aluminum alloy on CNC machine.
數控機床上的鋁合金保證25000孔 / 件
- Cost down & Increase life expectancy. 降低成本與增加壽命



TOPGREEN provides creative solutions and premium services necessary for the clients success and creates business values.

鑽鉅科技提供創造性的解決方案和優質的服務 成功地為客戶創造商業價值

整合需求·創造價值 Integrated Needs · Innovated Values

Roll Tap Series 擠壓型絲攻

◎ ○ Micro Roll Tap Series 微小徑擠壓型絲攻系列								
Thread Size 螺紋尺寸	TAP Limit 精度	e_c 無效牙	(L) Overall Length 全長	(ℓ) Thread Length 螺紋長	(Ds) Shank Diameter 柄徑	Material 材質	Stock 庫存	
S 0.5 x 0.125	TR2	2P	30	2	3	Carbide+SUS	※	
S 0.6 x 0.15	TR2	2P	30	2.5	3	Carbide+SUS	※	
S 0.7 x 0.175	TR2	2P	30	2.5	3	Carbide+SUS	※	
S 0.8 x 0.2	TR2	2P	30	3	3	Carbide+SUS	※	
S 0.8 x 0.15	TR2	2P	30	5	3	Carbide+SUS	※	
S 0.9 x 0.225	TR2	2P	30	3	3	Carbide+SUS	※	
○ Standard 標準品 ※ Produce by order 訂製品 (Unit 單位: mm)								
◎ ○ Roll Tap Series 擠壓型絲攻系列								
Thread Size 螺紋尺寸	TAP Limit 精度	e_c 無效牙	(L) Overall Length 全長	(ℓ) Thread Length 螺紋長	(Ds) Shank Diameter 柄徑	Material 材質	Stock 庫存	
M 1 x 0.25	TR4	2P	30	5	3	Carbide+SUS	○	
M 1.2 x 0.25	TR4	2P	30	5	3	Carbide+SUS	○	
M 1.4 x 0.3	TR4	2P	35	6.5	3	Carbide+SUS	○	
M 1.6 x 0.35	TR4	2P	35	7	3	Carbide+SUS	※	
M 1.7 x 0.35	TR4	2P	35	8	3	Carbide+SUS	※	
M 2 x 0.4	TR4	2P	40	8	3	Carbide+SUS	○	
M 2.3 x 0.4	TR4	2P	40	9	3	Carbide+SUS	※	
M 2.5 x 0.45	TR4	2P	45	9	3	Carbide+SUS	※	
M 2.6 x 0.45	TR4	2P	45	9.5	3	Carbide+SUS	※	
M 3 x 0.5	TR5	2P	45	9	4	Carbide+SUS	○	
M 3.5 x 0.6	TR4	2P	50	7.5	4	Carbide+SUS	○	
M 4.0 x 0.7	TR6	2P	50	8.5	※ 5 / 6	Carbide+SUS	○	
M 5.0 x 0.8	TR6	2P	60	9.5	※ 5.5 / 6	Carbide+SUS	○	
M 6.0 x 1.0	TR7	2P	60	12	6	Carbide+SUS	○	
M 7.0 x 1.0	TR6	2P	65	12	※ 6.2 / 8	Carbide+SUS	○	
M 8.0 x 1.25	TR7	2P	70	15	※ 6.2 / 8	Carbide+SUS	○	
M 8.0 x 1.0	TR7	2P	70	12	※ 6.2 / 8	Carbide+SUS	○	
M 10.0 x 1.5	TR7	2P	75	18	※ 7 / 8	Carbide+SUS	○	
M 10.0 x 1.25	TR7	2P	75	15	※ 7 / 8	Carbide+SUS	○	
M 10.0 x 1.0	TR7	2P	75	12	※ 7 / 8	Carbide+SUS	○	
M 12.0 x 1.75	TR8	2P	80	21	※ 8.5 / 10	Carbide+SUS	○	
M 12.0 x 1.5	TR7	2P	80	18	※ 8.5 / 10	Carbide+SUS	○	
M 12.0 x 1.25	TR7	2P	80	15	※ 8.5 / 10	Carbide+SUS	○	
M 12.0 x 1.0	TR7	2P	80	12	※ 8.5 / 10	Carbide+SUS	○	
M 14.0 x 2.0	TR10	2P	90	24	※ 10.5 / 12	Carbide+SUS	○	
M 14.0 x 1.5	TR9	2P	90	18	※ 10.5 / 12	Carbide+SUS	○	
M 16.0 x 2.0	TR10	2P	95	24	※ 12.5 / 14	Carbide+SUS	○	
M 16.0 x 1.5	TR9	2P	95	18	※ 12.5 / 14	Carbide+SUS	○	
M 18.0 x 2.5	TR11	2P	100	30	14	Carbide+SUS	○	
M 18.0 x 1.5	TR10	2P	100	18	14	Carbide+SUS	○	
M 20.0 x 2.5	TR11	2P	105	30	14 / 15 ※	Carbide+SUS	○	
M 20.0 x 1.5	TR10	2P	105	18	14 / 15 ※	Carbide+SUS	○	
○ Standard 標準品 ※ Produce by order 訂製品 (Unit 單位: mm)								

Low Carbon Steels 低碳鋼		Medium Carbon Steels 中碳鋼		High Carbon Steels 高碳鋼		Alloy Steels 合金鋼		Hardened Steels 硬化鋼		Stainless Steels 不銹鋼	Tool Steels 工具鋼	Cast Steels 鑄鋼	Cast Iron 鑄鐵	Ductile Cast Iron 韌性鑄鐵
C~0.25%		C0.25%~0.45%		C~0.45%		SCM		25~45 HRC	45~55 HRC	50~60 HRC	SUS	SKD	SC	FC
○	○	○	○	○	○	○	○				○	○		
Copper 銅	Brass 黃銅	Brass Casting 黃銅鑄物	Bronze 青銅	Aluminum Rolled 鋁擠壓材質	Aluminum Alloy Casting 鋁合金	Magnesium Alloy Casting 鎂合金	Zinc Alloy Casting 鋅合金	Titanium Alloy 鈦合金	Nickel Alloy Ni 基合金	Thermo Setting Plastic 熱硬化性塑膠	Thermo Plastic 熱可塑性塑膠			
Cu	Br	BrC	PB	AL	AC, ADC	MC	ZDC							
○	○	○		○	○		○	○						

◎ Excellent
○ Better

◎ Excellent
○ Better